

SIEMENS

Ingenuity for life



OpenAir™ Electronic Damper Actuators

More torque, greater energy efficiency, and long-lasting reliability gives you an ideal solution for all your HVAC equipment needs.

usa.siemens.com/openair

The right damper actuator for any HVAC application

A range that meets all your needs. Energy-efficient, simple, flexible and reliable: your benefits are at the heart of the entire damper actuator range, from smooth installation and rapid commissioning to operation that is both efficient and convenient. Save time and costs with OpenAir™



SPRING RETURN DAMPER ACTUATORS

A full range of spring return actuators, from 20 lb.-in. to 160 lb.-in., make OpenAir Damper Actuators the ideal OEM choice for economizer damper, roof top unit and air handling unit control. The 35 lb.-in. GPC Series actuator provides long lasting economizer control in a small footprint.



NON-SPRING RETURN DAMPER ACTUATORS

Achieve optimum VAV box control and greater energy efficiency. The GDE, GLB and GSD Damper Actuators feature the lowest power consumption on the market and the longest life cycle rating of 100,000 full stroke cycles and 5 million repetitions.




FAST-ACTING DAMPER ACTUATORS






The GAP and GNP are 50 lb.-in. fail-safe and fail-in-place damper actuators that are used in critical control environments such as lab and fume hood conditions. These fast-acting damper actuators operate with a runtime of 2 seconds, provide a wide variety of control signals with 24 VAC/DC operation and have plenum rated cabling.



FIRE AND SMOKE DAMPER ACTUATORS

The GJD and GRD damper actuators meet the UL555S standard. The damper manufacturers carry the UL555S listings with their assemblies (damper plus actuator). These actuators provide 15-second open/closed operation and 30-second motor drive operation at rated torque, temperature and voltage. Both actuators are integrated with Siemens electronic fusible link with three temperature ratings: 165°F, 212°F and 250°F.

Actuators for HVAC Applications		Control Signal	Operating Voltage	Standard Model	Pre-Cabled Terminal Strip (T); Extended 6 ft. Cable (Q)	Potentiometer (1 kOhm)	Adjustable Start Span	Adj. Start / Span + Two Auxiliary Switches	Two auxillary switches	Bulk Pack Available	Dimensions, Damper Shaft Round / Square (inch)
Spring Return Damper Actuators											
	GQD Series 20 lb-in (2 Nm) 30 s Runtime 15 s Spring Return	On/Off 2-Position	24 VAC/DC	GQD121.1P	—	—	—	—	GQD126.1P	GQD121.1P/B	R: 3/8" ... 1/2" Sq: 1/4" ... 7/16"
			120 VAC	GQD221.1U	—	—	—	—	GQD226.1U	GQD221.1U/B	
		Floating 3-Position	24 AC/DC	GQD131.1P	—	—	—	—	GQD136.1P	GQD131.1P/B	
		Modulating 0(2)-10 VDC / 10 - 0(2) DC	24 VAC/DC	GQD151.1P	—	—	—	—	GQD156.1P	GQD151.1P	
	GPC Series 35 lb-in (4 Nm) 60 s Runtime 15 s Spring Return	On/Off 2-Position	24 VAC/DC	GPC121.1P	—	—	—	—	GPC126.1P	—	R: 3/8" ... 1/2" Sq: 1/4" ... 7/16"
			100 to 240 VAC	GPC321.1U	—	—	—	—	GPC326.1P	—	
		Floating 3-Position	24 VAC/DC	GPC131.1P	—	—	—	—	GPC136.1P	—	
		Modulating 0(2)-10 VDC / 10 - 0(2) VDC	24 VAC/DC	GPC161.1P	—	—	—	—	GPC166.1P	—	
	GMA Series 62 lb-in (7 Nm) 90 s Runtime 15 s Spring Return	On/Off 2-Position	24 VAC/DC	GMA121.1U	—	—	—	—	GMA126.1U	—	R: 1/4" ... 3/4" Sq: 1/4" ... 1/2"
			120 VAC	GMA221.1U	—	—	—	—	GMA226.1U	—	
		Floating 3-Position	24 VAC/DC	GMA131.1U	—	GMA132.1U	—	—	GMA136.1U	—	
			—	GMA131.1P	—	—	—	—	—	—	
		Modulating 2 - 10 VDC	24 VAC/DC	GMA151.1U	—	—	—	—	GMA156.1U	—	
			—	GMA151.1P	—	—	—	—	GMA156.1P	—	
Modulating 0 - 10 VDC	24 VAC/DC	GMA161.1U	—	—	GMA163.1U	—	GMA166.1U	—			
		—	GMA161.1P	—	—	GMA163.1P	—	GMA166.1P	—		
	GCA Series 160 lb-in (18 Nm) 90 s Runtime 15 s Spring Return	On/Off 2-Position	24 VAC/DC	GCA121.1U	—	—	—	—	GCA126.1U	—	R: 3-8" ... 1" Sq: 1/4" ... 3/4"
			120 VAC	GCA221.1U	—	—	—	—	GCA226.1U	—	
		Floating 3-Position	24 VAC/DC	GCA131.1U	—	GCA132.1U	—	—	GCA136.1U	—	
			—	GCA131.1P	—	—	—	—	GCA136.1P	—	
		Modulating 0(2) - 10 VDC	24 VAC/DC	GCA151.1U	—	—	—	—	GCA156.1U	—	
			—	GCA151.1P	—	—	—	—	GCA156.1P	—	
		Modulating 0 - 10 VDC	24 VAC/DC	GCA161.1U	—	—	GCA163.1U	GCA164.1U	GCA166.1U	—	
			—	GCA161.1P	—	—	GCA163.1P	GCA164.1P	GCA166.1P	—	
Non-Spring Return Damper Actuators											
	GSD Series 20 lb-in (2 Nm) 30 s Runtime	On/Off & Floating 2-Position & 3-Position	24 VAC/DC	GSD141.1P	—	—	—	—	GSD146.1P	—	R: 3/8" ... 1/2" Sq: 1/4" ... 7/16"
			100 to 240 VAC	GSD341.1U	—	—	—	—	GSD346.1U	—	
		Modulating 0(2) - 10 VDC	24 VAC/DC	GSD161.1P	—	—	—	—	GSD166.1P	—	
	GDE Series 44 lb-in (5 Nm) 90 s Runtime	On/Off & Floating 2-Position & 3-Position	24 VAC	GDE141.1U	GDE141.1Q	—	—	—	GDE146.1U	GDE141.1U/B	R: 3/8" ... 5/8" Sq: 1/4" ... 1/2"
			100 to 240 VAC	GDE341.1U	—	—	—	—	GDE346.1U	—	
		Floating 3-Position	24 VAC	GDE131.1U	—	—	—	—	GDE136.1U	GDE131.1U/B	
			—	GDE131.1P	—	GDE132.1P	—	—	GDE136.1P	GDE131.1P/B	
		Modulating 0(2) - 10 VDC	24 VAC/DC	GDE161.1P	GDE161.1Q	—	GDE163.1P	GDE164.1P	GDE166.1P	GDE161.1P/B	
	GLB Series 88 lb-in (10 Nm) 150 s Runtime	On/Off & Floating 2-Position & 3-Position	24 VAC/DC	GLB141.1P	GLB141.1Q	—	—	—	GLB146.1P	—	R: 3/8" ... 5/8" Sq: 1/4" ... 1/2"
			100 to 240 VAC	GLB341.1U	—	—	—	—	GLB346.1U	—	
		Modulating 0(2) - 10 VDC	24 VAC/DC	GLB161.1P	GLB161.1Q	—	—	—	GLB166.1P	—	
	GEB Series 132 lb-in (15 Nm) 125 s Runtime	Floating 3-Position	24 VAC	GEB131.1U	—	GEB132.1U	—	—	GEB136.1U	—	R: 1/4" ... 3/4" Sq: 1/4" ... 1/2"
			—	GEB131.1P	—	—	—	—	—	—	
		Modulating 0(2) - 10 VDC	24 VAC	GEB161.1U	—	—	—	GEB164.1U	—	—	
	GBB Series 221 lb-in (25 Nm) 125 s Runtime	Modulating 0(2) - 10 VDC	24 VAC	GBB161.1U	—	—	GBB163.1U	GBB164.1U	GBB166.1U	—	R: 3/8" ... 1" Sq: 1/4" ... 5/8"
			—	GBB161.1P	—	—	GBB163.1P	GBB164.1P	GBB166.1P	—	
	GIB Series 310 lb-in (35 Nm) 125 s Runtime	Modulating 0(2) - 10 VDC	24 VAC	GIB161.1U	—	—	GIB163.1U	GIB164.1U	GIB166.1U	—	R: 3/8" ... 1" Sq: 1/4" ... 5/8"
			—	GIB161.1P	—	—	GIB163.1P	GIB164.1P	GIB166.1P	—	

Actuators for HVAC Applications	Control Signal	Operating Voltage	Standard Model	Pre-Cabled Terminal Strip (T); Extended 6 ft. Cable (Q)	Potentiometer (1 kOhm)	Adjustable Start Span	Adj. Start / Span + Two Auxiliary Switches	Two auxiliary switches	Bulk Pack Available	Dimensions, Damper Shaft Round / Square (inch)	
Fast-Acting Damper Actuators											
	GNP Series Fail-Safe 53 lb-in (6 Nm) 2 s Runtime 2 s Spring Return	On/Off 2-Position	24 VAC/DC	GNP191.1P	—	—	—	GNP196.1P	—	R: 1/4" ... 3/4" Sq: 1/4" ... 1/2"	
		Floating 3-Position									
		Modulating 0 (2) - 10 VDC 4 to 20 mA									
	GAP Series Fail-In-Place 53 lb-in (6 Nm) 2 s Runtime	On/Off 2-Position	24 VAC/DC	GAP191.1P	—	—	—	GAP196.1P	—	R: 1/4" ... 3/4" Sq: 1/4" ... 1/2"	
		Floating 3-Position									
		Modulating 0 (2) - 10 VDC 4 to 20 mA									
Fire and Smoke Damper Actuators											
	GJD Series 20 lb-in (2 Nm) 30 s Runtime <=15 s Spring Return	On/Off 2-Position	24 VAC/DC	GJD121.1U	—	—	—	—	GJD126.1U	—	R: 1/2"
			120 VAC	GJD221.1U	—	—	—	—	GJD226.1U	—	
			230 VAC	GJD321.1U	—	—	—	—	GJD326.1U	—	
	GRD Series 30 lb-in (3.4 Nm) 30 s Runtime <=15 s Spring Return	On/Off 2-Position	24 VAC/DC	GRD121.1U	—	—	—	—	GRD126.1U	—	R: 1/2"
			120 VAC	GRD221.1U	—	—	—	—	GRD226.1U	—	
			230 VAC	GRD321.1U	—	—	—	—	GRD326.1U	—	
Fire and Smoke Damper Accessories											
	Electronic Fusible Link (EFL)	165 °F Temperature Limit	ASK791.165								
		212 °F Temperature Limit	ASK791.212								
		250 °F Temperature Limit	ASK791.250								
		350 °F Temperature Limit	ASK791.350								



40+ Years
Innovating control actuators



15 Million+
OpenAir actuators installed in buildings worldwide



1.5 Million+
OpenAir reposition operations for longer life



25%
Lower power consumption



20%
More torque than the competition

Siemens Industry, Inc.
Building Products
1000 Deerfield Parkway
Buffalo Grove, IL 60089-4513
USA
Tel. 847-215-1000

Siemens Canada Limited Headquarters
1577 North Service Road East
Oakville, ON L6H 0H6
Canada
Tel. 905-465-8000

All rights reserved. Printed in USA 153-280 (06/19)
©2019 Siemens Industry, Inc.

Information in this publication is based on current specifications.
The company reserves the right to make changes in specifications
and models as design improvements are introduced.

OpenAir is a trademark of Siemens Industry, Inc.